



PTC Thermistor & 3 phase voltage preventer Series PD225

- Thermistor Relay combined with Protection against Phase Sequence, Phase Loss & Phase Asymmetry Faults
- Monitors and Protects Motors with Integrated PTC Resistor sensors
- Protection against Over heating for Heavy Duty Load, High Switching Frequency, High operating temperature & Insufficient cooling conditions
- LED indications for Healthy, Unhealthy, Sensor Open/Short and Phase Sequence fault conditions



Cat. No.		ML64BS	MLD7BS
Parameters			
Supply Voltage (Φ)		230 VAC (3 Phase 3 Wire)	400 VAC (3 Phase 3 Wire)
Supply Variation		-15% to + 15% (of Φ)	-15% to + 15% (of Φ)
Frequency		50/60 Hz	50/60 Hz
Power Consumption (Max.)		15 VA	24 VA
Trip Settings	Trip Level	2.7 kΩ, (± 5%)	
	Reset Level	1.71 kΩ, (± 5%)	
	Sensor Short	< 20Ω, (± 4Ω)	
	Hysteresis	40 Ω, (± 4Ω)	
	Sensor Open	> 20kΩ, (± 5%)	
Max Cold Res(Ω) of Sensor Chain		< 1.5 kΩ	
Cable Resistance		20 Ω	
Phase Asymmetry		70 VAC VAC(±)	104 VAC VAC(±)
Asymmetrical Phase Loss		110 VAC VAC(±)	220 VAC VAC(±)
Symmetrical Phase Loss		130 VAC VAC(±)	240 VAC VAC(±)
Restart Voltage		145 VAC (± 10 VAC)	265 VAC VAC(±)
Reset Mode		Auto	
Repeat Accuracy		1%	
Time Delay	Operate Time	< 350 ms	
	Release Time	360 - 550ms for Asymmetrical or Symmetrical Phase Fault & 100ms (max.) for Phase Sequence, Thermistor Trip	
	Reset Time	100 - 750 ms	
Output	Relay Output	1 NO (SPP) + 1 NO (PTC Thermistor)	1 NO (SPP) + 1 NC (PTC Thermistor)
	Contact Rating	5A 'NO' & 3A 'NC' @ 240 VAC / 28 VDC (Resistive)	
	Electrical Life	1 x 10 ⁵	
	Mechanical Life	3 x 10 ⁷	
Utilization Category	AC - 15	Rated Voltage (Ue): 120/240 V, Rated Current (Ie): 3.0/1.5 A	
	DC - 13	Rated Voltage (Ue): 24/125/250 V, Rated Current (Ie): 2.0/0.22/0.1 A	
LED Indications	(Green)	Continuous ON	Power Supply Healthy
		Continuous OFF	Power Fail
		Flashing	Sensor Open
	(Amber)	Continuous ON	Over Temperature Trip
		Continuous OFF	Thermistor Relay ON
		Flashing	Sensor Short or Cable Short
(Red)	Continuous ON	SPP Relay Trip (For Supply Above Restart Voltage)	
	Continuous OFF	SPP Relay ON (After ensuring the input Voltage of 5V above the Restart Voltage)	
	Flashing	Supply & SPP Fault below restart voltage	
Operating Temperature		- 10° C to +60° C	
Storage Temperature		- 15° C to +70° C	
Humidity (Non Condensing)		95% (Rh)	
Enclosure		Flame Retardant UL94-V0	
Dimension (W x H x D) (in mm)		22.5 X 83 X 100.5	
Weight (unpacked)		150 g	
Mounting		Base / DIN rail	
Certification		 	
Degree of Protection		IP 20 for Terminals, IP 40 for Enclosure	
EMI / EMC			
Harmonic Current Emissions		IEC 61000-3-2	
ESD		IEC 61000-4-2	
Radiated Susceptibility		IEC 61000-4-3	
Electrical Fast Transients		IEC 61000-4-4	
Surges		IEC 61000-4-5	
Conducted Susceptibility		IEC 61000-4-6	
Voltage Dips & Interruptions (AC)		IEC 61000-4-11	
Conducted Emission		CISPR 14-1	
Radiated Emission		CISPR 14-1	
Environmental			
Cold Heat		IEC 60068-2-1	
Dry Heat		IEC 60068-2-2	
Vibration		IEC 60068-2-6	
Repetitive Shock		IEC 60068-2-27	
Non-Repetitive Shock		IEC 60068-2-27	

ORDERING INFORMATION

Cat. No.	Description
ML64BS	230 VAC, PTC Thermistor & Single Phasing Preventer, 1 NO + 1 NO
ML67BS	230 VAC, PTC Thermistor & Single Phasing Preventer, 1 NO + 1 NC
MLD4BS	400 VAC, PTC Thermistor & Single Phasing Preventer, 1 NO + 1 NO
MLD7BS	400 VAC, PTC Thermistor & Single Phasing Preventer, 1 NO + 1 NC